

## COLLINS YOULDON CABLE DRUMS

### Cable Storage Units

Designed for heavy duty storage of electrical cable and small diameter hoses, these units are constructed in mild steel with a durable black nylon coating and tough thermoplastic feet.

All units may be stacked up to three high for maximum space saving. It is important to check the minimum bend radius of the cable/hose to avoid damage when wrapping around the drum core. Please see capacity chart below.

### CD1 Cable Storage Unit

The smallest unit in the range, with a 90 mm diameter drum core. Incorporates three cable supports, two connector clips and an integral winding knob.


The drum is retained on a cantilever axis by a spring catch. A carrying handle is incorporated into the top of the frame for easy handling.



### CD2, CD3, CD3.45 and CD3.6 Cable Storage Units

The larger CD2 and CD3 range are based on one design, with a 230 mm diameter drum core and varying drum widths for greater capacity.

The drum has four cable supports and two cable access points. A pin lock is fitted to the shaft to lock the drum when required. The winding handle rotates through 180 degrees for stowage.



**Capacity Chart overleaf – showing nominal capacity in metres (nominal capacity is 75% of theoretical maximum to allow for untidy winding)**

## COLLINS YOULDON CABLE DRUMS

Cable drum capacity chart (nominal capacity shown is 75% of theoretical maximum)

Cable diameter	6mm	8mm	10mm	12mm	16mm	20mm
CD1	150m	80m	50m	30m	-	-
CD2	300m	150m	100m	60m	30m	15m
CD3	600m	300m	200m	140m	60m	50m
CD3.45	1000m	500m	300m	200m	100m	60m
CD3.6	1300m	700m	400m	300m	140m	90m

Please contact our technical sales team for further information

+ AS Fire & Safety + Bayley + Collins Youldon

Tel: +44 1480 832200 | Fax: +44 1480 832233

[www.supplyplus.com](http://www.supplyplus.com)